

Safety  
Footwear



MONZA



## YEPA M090 WORK SHOE



EN ISO 20345:2011

**Category:** S2 or S3  
**Shoe Upper:** Original Printed Leather  
**Lining:** Air Lining  
**Inner Sole:** Removable and Antibacterial Inner Sole  
**Midssole:** K18 Zero Y Kevlar (1100N) (Optional)  
**Outsole:** PU/PU Dual Density Injection S C Passed  
**Outsole Features:** Shock Absorbing, Antitaatic, Oil Resistant  
**Toe Protection:** Optional (Seel or Composite Toe Cap) (200 Joule)  
**Size Range:** 36-47

## YEPA 1453 SUEDE WORK SHOE



EN ISO 20345:2011

**Category:** S1 or S1P  
**Shoe Upper:** Original Suede Leather  
**Lining:** Air Lining  
**Inner Sole:** Removable and Antibacterial Inner Sole  
**Midssole:** K18 Zero Y Kevlar (1100N) (Optional)  
**Outsole:** PU Single Density Injection  
**Outsole Features:** Shock Absorbing, Antitaatic, Oil Resistant  
**Toe Protection:** Steel Toe Cap (200 Joule)  
**Size Range:** 36-47

## YEPA 1453 LEATHER WORK SHOE



EN ISO 20345:2011

**Category:** S1 or S1P  
**Shoe Upper:** Original Leather  
**Lining:** Air Lining  
**Inner Sole:** Removable and Antibacterial Inner Sole  
**Midssole:** K18 Zero Y Kevlar (1100N) (Optional)  
**Outsole:** PU Single Density Injection  
**Outsole Features:** Shock Absorbing, Antitaatic, Oil Resistant  
**Toe Protection:** Steel Toe Cap (200 Joule)  
**Size Range:** 36-47

## YEPA M1020 SUEDE WORK SHOE



EN ISO 20345:2011

**Category:** S1 or S1P  
**Shoe Upper:** Original Suede Leather  
**Lining:** Air Lining  
**Inner Sole:** Removable and Antibacterial Inner Sole  
**Midssole:** K18 Zero Y Kevlar (1100N) (Optional)  
**Outsole:** PU/PU Dual Density Injection S C Passed  
**Outsole Features:** Shock Absorbing, Antitaatic, Oil Resistant  
**Toe Protection:** Optional (Seel or Composite Toe Cap) (200 Joule)  
**Size Range:** 36-47

## YEPA M1020 LEATHER WORK SHOE



EN ISO 20345:2011

**Category:** S1 or S1P  
**Shoe Upper:** Original Printed Leather  
**Lining:** Air Lining  
**Inner Sole:** Removable and Antibacterial Inner Sole  
**Midssole:** K18 Zero Y Kevlar (1100N) (Optional)  
**Outsole:** PU/PU Dual Density Injection S C Passed  
**Outsole Features:** Shock Absorbing, Antitaatic, Oil Resistant  
**Toe Protection:** Optional (Seel or Composite Toe Cap) (200 Joule)  
**Size Range:** 36-47

## YEPA MILANO WORK SHOE



EN ISO 20345:2011

**Category:** S1 or S1P  
**Shoe Upper:** Original Suede Leather and Textile  
**Lining:** Air Lining  
**Inner Sole:** Removable and Antibacterial Inner Sole  
**Midssole:** K18 Zero Y Kevlar (1100N) (Optional)  
**Outsole:** PU/PU Dual Density Injection S C Passed  
**Outsole Features:** Shock Absorbing, Antitaatic, Oil Resistant  
**Toe Protection:** Optional (Seel or Composite Toe Cap) (200 Joule)  
**Size Range:** 36-47

## YEPA 571 WORK SHOE



EN ISO 20345:2011

**Category:** S2 or S3  
**Shoe Upper:** Original Printed Leather  
**Lining:** Air Lining  
**Inner Sole:** Removable and Antibacterial Inner Sole  
**Midssole:** K18 Zero Y Kevlar (1100N) (Optional)  
**Outsole:** PU Dual Density Injection  
**Outsole Features:** Shock Absorbing, Antitaatic, Oil Resistant  
**Toe Protection:** Steel Toe Cap (200 Joule)  
**Size Range:** 36-47

## YEPA M090 TORCHMAN CAPPED WORK SHOE



EN ISO 20345:2011

**Category:** S2 or S3  
**Shoe Upper:** Original Printed Leather  
**Lining:** Air Lining  
**Inner Sole:** Removable and Antibacterial Inner Sole  
**Midssole:** K18 Zero Y Kevlar (1100N) (Optional)  
**Outsole:** PU/PU Dual Density Injection S C Passed  
**Outsole Features:** Shock Absorbing, Antitaatic, Oil Resistant  
**Toe Protection:** Optional (Seel or Composite Toe Cap) (200 Joule)  
**Size Range:** 36-47

## YEPA M1090 WORK BOOT



EN ISO 20345:2011

**Category:** S2 or S3  
**Shoe Upper:** Original Printed Leather  
**Lining:** Air Lining  
**Inner Sole:** Removable and Antibacterial Inner Sole  
**Midssole:** K18 Zero Y Kevlar (1100N) (Optional)  
**Outsole:** PU/PU Dual Density Injection S C Passed  
**Outsole Features:** Shock Absorbing, Antitaatic, Oil Resistant  
**Toe Protection:** Optional (Seel or Composite Toe Cap) (200 Joule)  
**Size Range:** 36-47

## YEPA 571 S2 WORK BOOT



EN ISO 20345:2011

**Category:** S2 or S3  
**Shoe Upper:** Original Printed Leather  
**Lining:** Air Lining  
**Inner Sole:** Removable and Antibacterial Inner Sole  
**Midssole:** K18 Zero Y Kevlar (1100N) (Optional)  
**Outsole:** PU Single Density Injection  
**Outsole Features:** Shock Absorbing, Antitaatic, Oil Resistant  
**Toe Protection:** Steel Toe Cap (200 Joule)  
**Size Range:** 36-47

## RIGEL 1703 WORK SHOE



EN ISO 20345:2011

**Category:** S1P or SBP  
**Shoe Upper:** Original Suede Leather  
**Lining:** Air Lining  
**Inner Sole:** Removable and Antibacterial Inner Sole  
**Midssole:** K18 Zero Y Kevlar (1100N) (Optional)  
**Outsole:** PU/PU Dual Density Injection S C Passed  
**Outsole Features:** Shock Absorbing, Antitaatic, Oil Resistant  
**Toe Protection:** Composite Toe Cap (200 Joule)  
**Size Range:** 36-47

## YEPA 1090 OILMAN WORK BOOT



EN ISO 20345:2011

**Category:** S2 or S3  
**Shoe Upper:** Original Printed Leather  
**Lining:** Air Lining  
**Inner Sole:** Removable and Antibacterial Inner Sole  
**Midssole:** K18 Zero Y Kevlar (1100N) (Optional)  
**Outsole:** PU/PU Dual Density Injection S C Passed  
**Outsole Features:** Shock Absorbing, Antitaatic, Oil Resistant  
**Toe Protection:** Optional (Seel or Composite Toe Cap) (200 Joule)  
**Size Range:** 36-47



## YEPA VERONA WORK SHOE



EN ISO 20345:2011

**Category:** S1 or S1P  
**Shoe Upper:** Original Suede Leather  
**Lining:** Air Lining  
**Inner Sole:** Removable and Antibacterial Inner Sole  
**Midssole:** K18 Zero Y Kevlar (1100N) (Optional)  
**Outsole:** PU/PU Dual Density Injection S C Passed  
**Outsole Features:** Shock Absorbing, Antitaatic, Oil Resistant  
**Toe Protection:** Optional (Seel or Composite Toe Cap) (200 Joule)  
**Size Range:** 36-47

## YEPA ROMA WORK SHOE



EN ISO 20345:2011

**Category:** S2 or S3  
**Shoe Upper:** Original Printed Leather And Textile  
**Lining:** Air Lining  
**Inner Sole:** Removable and Antibacterial Inner Sole  
**Midssole:** K18 Zero Y Kevlar (1100N) (Optional)  
**Outsole:** PU/PU Dual Density Injection S C Passed  
**Outsole Features:** Shock Absorbing, Antitaatic, Oil Resistant  
**Toe Protection:** Optional (Seel or Composite Toe Cap) (200 Joule)  
**Size Range:** 36-47

## YEPA MONZA WORK SHOE



EN ISO 20345:2011

**Category:** S2 or S3  
**Shoe Upper:** Original Printed Leather  
**Lining:** Air Lining  
**Inner Sole:** Removable and Antibacterial Inner Sole  
**Midssole:** K18 Zero Y Kevlar (1100N) (Optional)  
**Outsole:** PU/PU Dual Density Injection S C Passed  
**Outsole Features:** Shock Absorbing, Antitaatic, Oil Resistant  
**Toe Protection:** Optional (Seel or Composite Toe Cap) (200 Joule)  
**Size Range:** 36-47

## YEPA SIENA WORK SHOE



EN ISO 20345:2011

**Category:** S1 or S1P  
**Shoe Upper:** Original Printed Leather  
**Lining:** Air Lining  
**Inner Sole:** Removable and Antibacterial Inner Sole  
**Midssole:** K18 Zero Y Kevlar (1100N) (Optional)  
**Outsole:** PU/PU Dual Density Injection S C Passed  
**Outsole Features:** Shock Absorbing, Antitaatic, Oil Resistant  
**Toe Protection:** Optional (Seel or Composite Toe Cap) (200 Joule)  
**Size Range:** 36-47

# SER

We established Ser Footwear in 2018 as the foreign trade company of Yepar Footwear.

Yepar Footwear which established in 1992, produces safety shoes, military boots and shoes for crews at 4 different points in Istanbul and has an annual production capacity of 1 million pairs.

Our mission is to bring the right product to the right customer at the right price. Our vision is become a global company in the footwear industry.



| Symbol | Risk Covered   | EN ISO 20345:2011 |    |     |    |    |
|--------|--|-------------------|----|-----|----|----|
|        |  | SBP               | S1 | S1P | S2 | S3 |
| —      | Basic  | ✓                 | ✓  | ✓   | ✓  | ✓  |
| P      | Penetration resistance   |                   |    | ✓   |    | ✓  |
| A      | Antitaatic   | ★                 | ✓  | ✓   | ✓  | ✓  |
| E      | Energy Absorption Aound Heel   | ★                 | ✓  | ✓   | ✓  | ✓  |
| WRU    | Water Resistance of Upper  | ★                 |    |     | ✓  | ✓  |
| FO     | Resistance to Oil and Petrol   | ★                 | ✓  | ✓   | ✓  | ✓  |
| HRO    | Heat Resistance of Outsole (+300°C/Min)  | ★                 | ★  | ★   | ★  | ★  |
| SRC    | Slip Resistance On Ceramic Tile Floors with Sodium Lauly Sulfate Solution and On Seel Floors with Glycerol | ★                 | ★  | ★   | ★  | ★  |

★ → meets the specific requirement    ✓ → It is not requirement for standard but is optional